MARMIRO STONES®
BY TURAN BEKISOGLU

Product: Carya® Sandblasted Paver

Type: Marble

Origin: Turkey

Color: A creamy beige with wisps of red veins.

Sandblasted Finished: A lightly textured surface with modern, straight edges.

Recommended Installation Guidelines

TECHNICAL SPECIFICATIONS

Compressive Strength ASTM - C170

Sample	Antiqued	Sandblasted
Carya® Marble	N/A	10,325 psi

Flexural Strength ASTM - C880

Sample	Antiqued	Sandblasted
Carya® Marble	N/A	1,200 psi

Freeze and Thaw ASTM - C666

Sample	Results	Notes
Carya® Marble	Pass	No cracks or deformations noted.

Water Absorption ASTM - C97

Sample	Antiqued Water Absorption %	Sandblasted Water Absorption %
Carya® Marble	N/A	0.83%

Density ASTM - C97

Sample	Antiqued Density	Sandblasted Density
Carya® Marble	N/A	168.5 lbs/ft³

DISCLAIMER

Marmiro Stones, Inc. has no control over the buyer's selection or use of any stone. Prior to using or permitting the use of our products, the buyer must determine the suitability of the products for the intended use and assumes all risk and liability whatsoever in connection therewith. The buyer must also determine the slip resistance suitability and maintainability as Marmiro Stones, Inc. is not responsible for any losses or damages sustained by the buyer, or any other person, as a result of improper installation or misapplication of our products. Please refer to the ASTM standards for more specific information concerning stone or paver specifications. Marmiro Stones, Inc. and its agents and employees are held harmless against any loss, damage, claim, suit, liability, judgement, or expense arising out of, or in connection with, any injury, damage, or loss to any property, or violation of any applicable laws or regulations resulting from, or in connection with, the sale, transportation, installation, or use of our products by the buyer.